

Frame	Magflow® injection moulded magnesium
Colour	So White
Head Angle	70°
Seat Tube Angle	68°
Wheelbase	1065mm (42in)
Bottom Bracket Height	275mm (11.5in)
Transmission	Cleandrive® fully sealed 3-speed sequential gearbox
Wheels	PitstopWheel® side-mounted Magflow®
Tyres	Gocycle® Vredestein with reflector side wall, 406-47/20-1.75in (BMX)
Brakes	Gocycle integrated floating disk mechanical
Front Suspension	Fixed
Rear Suspension	Gocycle Lockshock™ 25mm (1in) travel
Seat Tube	Vgonomic™ inline height adjustable
Saddle	Velo D2 Comfort
Stem	Vgonomic™ height and reach adjustable
Motor	Gocycle 250 Watt continuous
Battery	9Ah NiMH
Controller	Gocycle proprietary
Charger	3.5 hour full recharge
Range	EU mode: 13km – 32km (8 – 20 miles) depending on pedal input USA mode: 9km – 32km (6 – 20 miles) depending on pedal input
Speed	EU mode: 24km/h (15mph) USA mode: 29km/h (18mph)
Stowable Dimensions	650mm x 540mm x 260mm (25.5in x 21.2in x 10.2in), including motor, battery and charger
Weight	16.2kg (35.6 lbs), including mudguards and Empower Pack 11.9kg (26.2 lbs), excluding mudguards and Empower Pack
Max Rider Weight	100kg (220 lbs), including clothing and backpack